

View Online at <https://aerobasegroup.com/nsn/4320-01-451-4157>

**Mounting Type:**

Flange

**Cylinder Quantity:**

9

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Drive Connection Type:**

Rigid coupled

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Pumping Element Type:**

Piston

**End Application:**

2430-01-423-2819; w/s code 97

**Maximum Discharge Flow Rate:**

21.0 gallons per minute

**Discharge Pressure:**

2700.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1800.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Counterclockwise

**Pump Reciprocating Design:**

Single acting

**Reciprocating Stroke Type:**

Variable

**Volume Control Type:**

Pressure compensation

**Control Location:**

Left side

**Drive Shaft Type:**

Splined, involute external

**Drive Shaft Length:**

1.375 inches

**Discharge Connection Thread Size And Series/type Designator:**

1.3125-12 un

**Intake Connection Thread Size And Series/type Designator:**

1.875-12 un

**Special Features:**

Buna-n seals; load sensing compensator and pressure limiter with a 0.4375-20 unf-2b port; sae 'b' mounting flange; 0.875-14 unf-2b drain port

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400