

View Online at <https://aerobasegroup.com/nsn/4320-01-451-4157>

Mounting Type:

Flange

Cylinder Quantity:

9

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Drive Connection Type:

Rigid coupled

Media For Which Designed:

Hydrocarbon fuels and oils

Pumping Element Type:

Piston

End Application:

2430-01-423-2819; w/s code 97

Maximum Discharge Flow Rate:

21.0 gallons per minute

Discharge Pressure:

2700.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1800.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Counterclockwise

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Variable

Volume Control Type:

Pressure compensation

Control Location:

Left side

Drive Shaft Type:

Splined, involute external

Drive Shaft Length:

1.375 inches

Discharge Connection Thread Size And Series/type Designator:

1.3125-12 un

Intake Connection Thread Size And Series/type Designator:

1.875-12 un

Special Features:

Buna-n seals; load sensing compensator and pressure limiter with a 0.4375-20 unf-2b port; sae 'b' mounting flange; 0.875-14 unf-2b drain port

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400