

View Online at <https://aerobasegroup.com/nsn/4320-01-452-0152>

Mounting Type:

Flange

Intake Connection Quantity:

2

Intake Connection Type:

Threaded internal and unthreaded internal

Discharge Connection Quantity:

2

Discharge Connection Type:

Threaded internal and unthreaded internal

Drive Connection Type:

Rigid coupled

End Application:

Navy weapons code ka, usns stalwart class tagos

Maximum Discharge Flow Rate:

6.0 gallons per minute

Operating Speed At Rated Capacity:

1800.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Clockwise and counterclockwise

Rotary Pump Design:

Gear

Operation Method:

Powered

Drive Shaft Type:

Tongue

Drive Shaft End Diameter:

Between 0.4987 inches and 0.4992 inches

Drive Shaft Length:

1.250 inches

Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Special Features:

Kcartridge pump; automatic reversing feature; shaft tang end 0.308" - 0.310" thick by 0.37" long; four 0.34" diameter mounting holes; has internal and external ports; internal ports are two 1.00" diameter unthreaded holes

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400