## NSN 4320-01-453-2133

Centrifugal Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-453-2133

| Mounting Type:   |
|--|
| Base   |
|  |
| Stage Quantity:  |
| Intake Connection Quantity:                                  |
| 1  |
| Intake Connection Type:                                      |
| Threaded internal  |
| Discharge Connection Quantity:                               |
| 1  |
| Discharge Connection Type:                                   |
| Threaded internal  |
| Drive Connection Type:                                       |
| Close coupled  |
| Media For Which Designed:                                    |
| Water, fresh and water, salt and water, waste                |
| Maximum Discharge Flow Rate:                                 |
| 160.0 gallons per minute                                     |
| Total Head:  |
| 60.000 feet  |
| Operating Speed At Rated Capacity:                           |
| 3450.0 revolutions per minute                                |
| Pumping Element Operating Position:                          |
| Horizontal   |
| Pump Rotation Direction:                                     |
| Counterclockwise   |
| Centrifugal Pump Design:                                     |
| Mixed flow   |
| Centrifugal Pump Impeller Quantity:                          |
| 1  |
| Centrifugal Pump Impeller Suction Type:                      |
| Single   |
| Discharge Connection Thread Size And Series/type Designator: |
| 1.500-11-1/2 npt   |
| Intake Connection Thread Size And Series/type Designator:    |
| 2.000-11-1/2 npt   |
| Special Features:  |
| Clutch driven, all bronze                                    |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 4320-01-453-2133

Centrifugal Pump - Page 2 of 2



Demilitarization:

No

Fiig:

A19400