

View Online at <https://aerobasegroup.com/nsn/4320-01-453-7951>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, salt

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Navy weapons code th, strategic sealift conversion ships class

Maximum Discharge Flow Rate:

1000.0 gallons per minute

Total Head:

67.000 feet

Operating Speed At Rated Capacity:

1760.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

24.5

Prime Mover Power Rating:

25.0 horsepower

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Worthington seawater service pump; 6in. Suction flange; 5in. Discharge flange

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400