

View Online at <https://aerobasegroup.com/nsn/4320-01-455-9199>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Flange

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Rectangular flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Pump Quantity:**

1

**Cooling Method:**

Blower cooled

**End Application:**

Navy weapons code jx, avenger class mcm

**Maximum Discharge Flow Rate:**

2.0 gallons per minute

**Total Head:**

20.000 feet

**Operating Speed At Rated Capacity:**

1750.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Double

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

1.0 and 0.9 and 0.5

**Discharge Connection Thread Size And Series/type Designator:**

1.000-11-1/2 npt

**Prime Mover Power Rating:**

0.5 horsepower

**Voltage In Volts:**

208.0 and 230.0 and 460.0

**Phase:**

Three

**Special Features:**

Model t41c all bronze condensate pump unit mounted by its 7.5in. X 4.5in. Suction aurora flange to an included 18in. W x 18in. D x 12in. H 304 stainless steel receiver tank; also includes a square d switch modified with a stainless steel bushing

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400