

View Online at <https://aerobasegroup.com/nsn/4320-01-455-9199>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Flange

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Rectangular flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Cooling Method:

Blower cooled

End Application:

Navy weapons code jx, avenger class mcm

Maximum Discharge Flow Rate:

2.0 gallons per minute

Total Head:

20.000 feet

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Double

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.0 and 0.9 and 0.5

Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Prime Mover Power Rating:

0.5 horsepower

Voltage In Volts:

208.0 and 230.0 and 460.0

Phase:

Three

Special Features:

Model t41c all bronze condensate pump unit mounted by its 7.5in. X 4.5in. Suction aurora flange to an included 18in. W x 18in. D x 12in. H 304 stainless steel receiver tank; also includes a square d switch modified with a stainless steel bushing

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400