NSN 4320-01-456-3622

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-456-3622

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Base
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Water, salt
Pump Quantity:
rump quantity.
1
1
1 Cooling Method:
1 Cooling Method: Blower cooled
1 Cooling Method: Blower cooled End Application:
1 Cooling Method: Blower cooled End Application: Distiller
Cooling Method: Blower cooled End Application: Distiller Maximum Discharge Flow Rate:
Cooling Method: Blower cooled End Application: Distiller Maximum Discharge Flow Rate: 58.0 gallons per minute
Cooling Method: Blower cooled End Application: Distiller Maximum Discharge Flow Rate: 58.0 gallons per minute Discharge Pressure:
Cooling Method: Blower cooled End Application: Distiller Maximum Discharge Flow Rate: 58.0 gallons per minute Discharge Pressure: 55.0 pounds per square inch gage
Cooling Method: Blower cooled End Application: Distiller Maximum Discharge Flow Rate: 58.0 gallons per minute Discharge Pressure: 55.0 pounds per square inch gage Total Head:
Cooling Method: Blower cooled End Application: Distiller Maximum Discharge Flow Rate: 58.0 gallons per minute Discharge Pressure: 55.0 pounds per square inch gage Total Head: 127.000 feet
Cooling Method: Blower cooled End Application: Distiller Maximum Discharge Flow Rate: 58.0 gallons per minute Discharge Pressure: 55.0 pounds per square inch gage Total Head: 127.000 feet Operating Speed At Rated Capacity:
Cooling Method: Blower cooled End Application: Distiller Maximum Discharge Flow Rate: 58.0 gallons per minute Discharge Pressure: 55.0 pounds per square inch gage Total Head: 127.000 feet Operating Speed At Rated Capacity: 3555.0 revolutions per minute
Cooling Method: Blower cooled End Application: Distiller Maximum Discharge Flow Rate: 58.0 gallons per minute Discharge Pressure: 55.0 pounds per square inch gage Total Head: 127.000 feet Operating Speed At Rated Capacity: 3555.0 revolutions per minute Pumping Element Operating Position:
Cooling Method: Blower cooled End Application: Distiller Maximum Discharge Flow Rate: 58.0 gallons per minute Discharge Pressure: 55.0 pounds per square inch gage Total Head: 127.000 feet Operating Speed At Rated Capacity: 3555.0 revolutions per minute Pumping Element Operating Position: Horizontal
Cooling Method: Blower cooled End Application: Distiller Maximum Discharge Flow Rate: 58.0 gallons per minute Discharge Pressure: 55.0 pounds per square inch gage Total Head: 127.000 feet Operating Speed At Rated Capacity: 3555.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design:
Cooling Method: Blower cooled End Application: Distiller Maximum Discharge Flow Rate: 58.0 gallons per minute Discharge Pressure: 55.0 pounds per square inch gage Total Head: 127.000 feet Operating Speed At Rated Capacity: 3555.0 revolutions per minute Pumping Element Operating Position: Horizontal Centrifugal Pump Design: Mixed flow

Single

NSN 4320-01-456-3622

Centrifugal Pump Unit - Page 2 of 2

A19400



Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Current Rating In Amps:
6.4
Prime Mover Power Rating:
5.0 horsepower
Voltage In Volts:
440.0
Phase:
Three
Special Features:
Close coupled distiller feed water pump unit updated with a reliance m/p 801626-505 navy.A.Motor
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: