

View Online at <https://aerobasegroup.com/nsn/4320-01-456-3622>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, salt

Pump Quantity:

1

Cooling Method:

Blower cooled

End Application:

Distiller

Maximum Discharge Flow Rate:

58.0 gallons per minute

Discharge Pressure:

55.0 pounds per square inch gage

Total Head:

127.000 feet

Operating Speed At Rated Capacity:

3555.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

6.4

Prime Mover Power Rating:

5.0 horsepower

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Close coupled distiller feed water pump unit updated with a reliance m/p 801626-505 navy.A.Motor

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400