

View Online at <https://aerobasegroup.com/nsn/4320-01-456-4759>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Navy weapons codeja, nimitz class cvn

Maximum Discharge Flow Rate:

9.0 gallons per minute and 8.5 gallons per minute

Discharge Pressure:

40.0 pounds per square inch gage

Total Head:

92.000 feet

Operating Speed At Rated Capacity:

1725.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Vane

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.5

Prime Mover Power Rating:

1.5 horsepower

Product Name:

Motor driven auxiliary lube oil pump

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Auxiliary lube oil pumping unit - main feed pump

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400