

View Online at <https://aerobasegroup.com/nsn/4320-01-456-5100>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Environmental Protection:**

Drip-proof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**End Application:**

Pc-10

**Maximum Discharge Flow Rate:**

5.2 gallons per minute

**Discharge Pressure:**

150.0 pounds per square inch gage

**Suction Lift:**

20.000 feet

**Operating Speed At Rated Capacity:**

1150.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Gear

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Current Rating In Amps:**

13.0 and 6.5

**Discharge Connection Thread Size And Series/type Designator:**

0.500-14 npt

**Intake Connection Thread Size And Series/type Designator:**

0.500-14 npt

**Prime Mover Power Rating:**

2.0 horsepower

**Voltage In Volts:**

115.0 and 230.0

**Phase:**

Single

**Special Features:**

Close coupled; bronze; pump has built-in adjustable relief valve

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400