NSN 4320-01-457-5490

Rotary Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-457-5490

| Manustina Tonos |
|--|
| Mounting Type: |
| Flange |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Rectangular flange |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Rectangular flange |
| Drive Connection Type: |
| Rigid coupled |
| Maximum Discharge Flow Rate: |
| 8.43 gallons per minute and 6.18 gallons per minute |
| Discharge Pressure: |
| 0.0 pounds per square inch gage and 3500.0 pounds per square inch gage |
| Operating Speed At Rated Capacity: |
| 1500.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Pump Rotation Direction: |
| Counterclockwise |
| Rotary Pump Design: |
| Vane |
| Operation Method: |
| Powered |
| Drive Shaft Type: |
| Key type, external |
| Drive Shaft End Diameter: |
| Between 0.873 inches and 0.875 inches |
| Drive Shaft Length: |
| 2.110 inches |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A19400 |