

View Online at <https://aerobasegroup.com/nsn/4320-01-458-9230>

Pressure Rating:

2500.0 pounds per square inch

Voltage In Volts And Current Type:

460.0 ac

General Description:

Pump assembly includes: 1 electric motor p/n 41520 and 1 pump p/n pvwh34-rsas-cn; ratings: safety factor, structural 6: 1; safety factor, wire rope 5: 1; load 5, 700lbs; hoist speed 85fpm nomina (bds); swing speed 2rmp nonimal; swing arc 135 degrees each direction from center; wire rope 5/8in 6 x 37 eips rr-w-410 type 1 class 3 strength 32200lbs; hook 8800 lbs capacity, auto release; test weights: dynamic 9000lbs; static 12000; electrical power requirements: 460 vac, 3-phase, 60hz; hydraulic power unit: pump axial piston, pressure comp. And vari displace.; motor 50hp, 1750rpm; return filter in tank, 6 micron element; tank 100 gal cap; hydraulic system: operating pressure 2500psi; relief pressure 2750psi; req pump output 34gpm; temp range o(f) to 180(f); hydraulic fluid mil-h-17672(mobil dte 13m) ; control valve: 4-section lever actuated and electro/hydraulic proportional; boom: double acting; winch: maximum rated load 5700lbs; normal hoist speed 85-100fpm

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23900