## NSN 4320-01-459-2260

Reciprocating Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-459-2260

Cylinder Quantity:
1
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Drive Connection Type:
Rigid coupled
Pumping Element Type:
Piston
Discharge Pressure:
2250.0 pounds per square inch gage
Pumping Element Operating Position:
Horizontal
Pump Reciprocating Design:
Double acting
Reciprocating Stroke Type:
Variable
Operation Method:
Manual
Drive Shaft Type:
Plain round
Drive Shaft End Diameter:
1.000 inches
Discharge Connection Thread Size And Series/type Designator:
0.438-20 un
Product Name:
Republic hand pump
Special Features:
Lightweight, double-acting pump delivering 0.7 cubic inch per cycle (2strokes); integral resilient seated valves prevent back flow during
operation; service application: hydraulic oil; working pressure range: 0.0 to 3000 psi 3000 psi based on 60 lbs. Handle force at 22-1/2 in.);
proof pressure: 4.500 psi; burst pressure: 7500 psi; temperature range: -65 to 250 degrees f.; same as model part number 916-8d27,
nsn 4320-01-345-3940, except pivot arm is turned upside down for use as an emergency pump for landing gear
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
A19400