

View Online at <https://aerobasegroup.com/nsn/4320-01-464-7690>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Flange

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Unthreaded external

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded external

Current Type:

Ac

Media For Which Designed:

Water, fresh and ethylene glycol

Environmental Protection:

Submersible

Pump Quantity:

1

Cooling Method:

Water cooled

End Application:

Fire fighting

Maximum Discharge Flow Rate:

3.0 gallons per minute

Discharge Pressure:

2.0 pounds per square inch gage

Total Head:

4.600 feet

Operating Speed At Rated Capacity:

3200.0 revolutions per minute

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Unpackaged Unit Length:

2.900 inches

Unpackaged Unit Width:

4.4400 inches

Unpackaged Unit Height:

4.220 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

0.23

Prime Mover Power Rating:

0.005 horsepower

Voltage In Volts:

230.0

Phase:

Single

Special Features:

Max intake pressure 50 psi; material in contact w/ solution: polypropylene, nylon, buna-n, 316 stainless steel, ceramic magnet, chemloy washer; material not in contact w/ solution: epoxy, noryl; stainless steel base; no plug (standard)

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400