

View Online at <https://aerobasegroup.com/nsn/4320-01-464-7690>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Flange

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Unthreaded external

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Unthreaded external

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh and ethylene glycol

**Environmental Protection:**

Submersible

**Pump Quantity:**

1

**Cooling Method:**

Water cooled

**End Application:**

Fire fighting

**Maximum Discharge Flow Rate:**

3.0 gallons per minute

**Discharge Pressure:**

2.0 pounds per square inch gage

**Total Head:**

4.600 feet

**Operating Speed At Rated Capacity:**

3200.0 revolutions per minute

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Unpackaged Unit Length:**

2.900 inches

**Unpackaged Unit Width:**

4.4400 inches

**Unpackaged Unit Height:**

4.220 inches

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Current Rating In Amps:**

0.23

**Prime Mover Power Rating:**

0.005 horsepower

**Voltage In Volts:**

230.0

**Phase:**

Single

**Special Features:**

Max intake pressure 50 psi; material in contact w/ solution: polypropylene, nylon, buna-n, 316 stainless steel, ceramic magnet, chemloy washer; material not in contact w/ solution: epoxy, noryl; stainless steel base; no plug (standard)

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400