

View Online at <https://aerobasegroup.com/nsn/4320-01-477-7612>

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Maximum Discharge Flow Rate:

150.0 gallons per minute

Discharge Pressure:

190.0 kilograms per square centimeter gage

Total Head:

25.000 feet

Suction Lift:

190.000 feet

Operating Speed At Rated Capacity:

3600.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Counterclockwise

Centrifugal Pump Impeller Quantity:

1

Intake Connection Thread Size And Series/type Designator:

1.500-8 npt

Special Features:

Pump specifications: housing, and impeller: cast iron class 30 or bronze, suction and discharge: 1.5"x2" npt pipe sizes, cast iron class 30 or bronze, volute: cast iron class 30 or bronze, replaceable, adaptor: cast iron class 30 or bronze p.E.M. Or cc motor, drive sleeve: stainless steel 300 series, seal: standard john crane type-21 carbon, ceramic, stainless steel and viton with other options available, fasteners: stainless steel 300 series

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400