

View Online at <https://aerobasegroup.com/nsn/4320-01-484-1322>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Dc

Media For Which Designed:

Water, fresh and water, salt

Environmental Protection:

Watertight

Pump Quantity:

1

Cooling Method:

Self ventilated

End Application:

Pneumatic tire roller model no. 9pc-12d-5167-5184

Maximum Discharge Flow Rate:

2.4 gallons per minute

Discharge Pressure:

4.3 pounds per square inch gage

Total Head:

50.000 feet

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

0

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

5.0

Discharge Connection Thread Size And Series/type Designator:

0.375-18 npt

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

100.0 watts

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400