

View Online at <https://aerobasegroup.com/nsn/4320-01-486-4476>

**Prime Mover Quantity:**

1

**Intake Connection Quantity:**

1

**Discharge Connection Quantity:**

1

**Current Type:**

Ac/dc

**Media For Which Designed:**

Liquid and sewage

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**End Application:**

Next generation radar (nexrad)

**Maximum Discharge Flow Rate:**

6.0 gallons per minute

**Total Head:**

40.000 feet

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

2

**Unpackaged Unit Length:**

6.375 inches

**Unpackaged Unit Width:**

4.0000 inches

**Unpackaged Unit Height:**

3.500 inches

**Prime Mover Type:**

Electric motor

**Current Rating In Amps:**

1.7

**Features Provided:**

Self-priming

**Voltage In Volts:**

115.0

**Special Features:**

Self primes to 10 ft; buna n impellers and lip type seals; motor has thermal protection and external brush holders; dual threaded inlet and outlet; 3/8 id npt 3/4 od hose thread; water temp range 40 to 140 degrees f; includes two extra impellers and gaskets; for intermittent use only; 6 ft 3 cond cord; 48.3 ft shut off; teel brand mdoel 360

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400