

View Online at <https://aerobasegroup.com/nsn/4320-01-486-4476>

Prime Mover Quantity:

1

Intake Connection Quantity:

1

Discharge Connection Quantity:

1

Current Type:

Ac/dc

Media For Which Designed:

Liquid and sewage

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Next generation radar (nexrad)

Maximum Discharge Flow Rate:

6.0 gallons per minute

Total Head:

40.000 feet

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

2

Unpackaged Unit Length:

6.375 inches

Unpackaged Unit Width:

4.0000 inches

Unpackaged Unit Height:

3.500 inches

Prime Mover Type:

Electric motor

Current Rating In Amps:

1.7

Features Provided:

Self-priming

Voltage In Volts:

115.0

Special Features:

Self primes to 10 ft; buna n impellers and lip type seals; motor has thermal protection and external brush holders; dual threaded inlet and outlet; 3/8 id npt 3/4 od hose thread; water temp range 40 to 140 degrees f; includes two extra impellers and gaskets; for intermittent use only; 6 ft 3 cond cord; 48.3 ft shut off; teel brand mdoel 360

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400