

View Online at <https://aerobasegroup.com/nsn/4320-01-491-2892>

Cylinder Quantity:

1

Discharge Connection Type:

Threaded internal

Pump Quantity:

1

Pumping Element Type:

Piston

Discharge Pressure:

60.0 pounds per square inch gage

Operating Speed At Rated Capacity:

235.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Reciprocating Stroke Type:

Variable

Product Name:

March metering pumps positive displacement piston type

Special Features:

Flow rate: 50 cc to 1000 cc; self priming even when dry, fully adjustable while running, pump will pump to pressure up to 160 psi and have a suction vacuum of 20 in. Will handle and dispense wide variety of liquid mild and non corrosive chemicals, algecides, phosphatge and chromate solutions for water treating. Will dispense both wetting agents and liquid detergents as rinse aid, cleaning and spot removing agent. Will pump a variety of metal processing, plating and finishing chemicals. Rylon piston w/ 3 o rings and polytetrafluoroethylene rings. Pump body and magnetic valve chocks are rylon. Motor is thermal overload protected, 115 v, h0-hz, and comes w/ 6 ft. 3-2843 cord and plug . Inlet 1/4" fpt, outlet: 1/4" fpt, hp: 1/50 motor rpm: 235, watts: 50

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400