

View Online at <https://aerobasegroup.com/nsn/4320-01-491-2892>

**Cylinder Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Pump Quantity:**

1

**Pumping Element Type:**

Piston

**Discharge Pressure:**

60.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

235.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Reciprocating Stroke Type:**

Variable

**Product Name:**

March metering pumps positive displacement piston type

**Special Features:**

Flow rate: 50 cc to 1000 cc; self priming even when dry, fully adjustable while running, pump will pump to pressure up to 160 psi and have a suction vacuum of 20 in. Will handle and dispense wide variety of liquid mild and non corrosive chemicals, algecides, phosphatge and chromate solutions for water treating. Will dispense both wetting agents and liquid detergents as rinse aid, cleaning and spot removing agent. Will pump a variety of metal processing, plating and finishing chemicals. Rylon piston w/ 3 o rings and polytetrafluoroethylene rings. Pump body and magnetic valve chocks are rylon. Motor is thermal overload protected, 115 v, h0-hz, and comes w/ 6 ft. 3-2843 cord and plug . Inlet 1/4" fpt, outlet: 1/4" fpt, hp: 1/50 motor rpm: 235, watts: 50

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400