

View Online at <https://aerobasegroup.com/nsn/4320-01-493-4731>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Cylinder Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Pump Quantity:

1

Pumping Element Type:

Diaphragm

Cooling Method:

Air to air cooled

End Application:

Backwash pump assembly for the 3k rowpu

Maximum Discharge Flow Rate:

2.0 gallons per minute

Discharge Pressure:

50.0 pounds per square inch gage

Suction Lift:

8.000 feet

Pumping Element Operating Position:

Horizontal

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Fixed

Inclosure Type:

Partially enclosed

Discharge Connection Thread Size And Series/type Designator:

0.375-18 npt

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt

Prime Mover Power Rating:

57.5 watts

Voltage In Volts:

115.0

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400