

View Online at <https://aerobasegroup.com/nsn/4320-01-493-4731>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Cylinder Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Pump Quantity:**

1

**Pumping Element Type:**

Diaphragm

**Cooling Method:**

Air to air cooled

**End Application:**

Backwash pump assembly for the 3k rowpu

**Maximum Discharge Flow Rate:**

2.0 gallons per minute

**Discharge Pressure:**

50.0 pounds per square inch gage

**Suction Lift:**

8.000 feet

**Pumping Element Operating Position:**

Horizontal

**Pump Reciprocating Design:**

Single acting

**Reciprocating Stroke Type:**

Fixed

**Inclosure Type:**

Partially enclosed

**Discharge Connection Thread Size And Series/type Designator:**

0.375-18 npt

**Intake Connection Thread Size And Series/type Designator:**

0.375-18 npt

**Prime Mover Power Rating:**

57.5 watts

**Voltage In Volts:**

115.0

**Phase:**

Single

**Frequency In Hertz:**

50.0 and 60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400