

View Online at <https://aerobasegroup.com/nsn/4320-01-495-3441>

**Cylinder Quantity:**

0

**Intake Connection Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Pumping Element Type:**

Diaphragm

**Maximum Discharge Flow Rate:**

35.0 gallons per minute

**Discharge Pressure:**

120.0 pounds per square inch gage

**Suction Lift:**

20.000 feet

**Pumping Element Operating Position:**

Horizontal

**Reciprocating Stroke Type:**

Fixed

**Operation Method:**

Powered

**Product Name:**

Metallic diaphragm pump

**Special Features:**

Ratio: 1: 1, displacement gallons: 0.16, air inlet: 1/4-inch np (f), fluid inlet: 1-inch npt(f) , fluid outlet: 1 inch npt, weight: 31 lbs, base model: 6661 1" ball, air motor: cast iron, wetted parts: 316 ss, check valve seats: 316 ss, ball check/diaphragm: polytetrafluoroethylene, pump must mounted with feet to ground, pump contains an air valve vs. A cylinder and a double diaphragm; suction lift listed is dry suction lift only

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400