

View Online at <https://aerobasegroup.com/nsn/4320-01-502-2568>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Environmental Protection:

Drip-proof

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Recirculating loop chiller

Maximum Discharge Flow Rate:

150.0 gallons per minute

Discharge Pressure:

125.0 pounds per square inch gage

Total Head:

150.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

4.2 and 2.1

Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Prime Mover Power Rating:

1.0 horsepower

Voltage In Volts:

208.0 and 230.0 and 460.0

Phase:

Three

Special Features:

Metal parts made from stainless steel 316 ss; impeller diameter 5-3/16 in nom; 212.0 degrees f maximum temp; driver 3ph open, drip-proof

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400