

View Online at <https://aerobasegroup.com/nsn/4320-01-509-4275>

Stage Quantity:

1

Intake Connection Quantity:

2

Discharge Connection Quantity:

1

Media For Which Designed:

Water, waste

End Application:

Refrigerator

Maximum Discharge Flow Rate:

1.5 gallons per minute

Suction Lift:

18.000 feet

Operating Speed At Rated Capacity:

3000.0 revolutions per minute

Pump Rotation Direction:

Clockwise

Centrifugal Pump Design:

Axial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Product Name:

Condensate pump

Special Features:

Abs plastic reservoir; thermally protected motor with 300 series s.S. Shaft, 2.625 in. Dia. With key; built-in full flow check valve for 0.375 in id plastic tubing; 6 ft. Power cord with molded plug (nema 5-15p or 6-15p); 1/20 hp. Motor; 115v 1.7a/230v 0.9a; 2 inlets 1.0 in. And 1.375 in.; 0.375 in. Discharge size; 1 quart reservoir; 9.25 in. W x 5.5 in. D x 5.25 in. H; 1.75 in. Inlet height; 110 degree f max. Temperature; 5 lbs. Weight

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400