

View Online at <https://aerobasegroup.com/nsn/4320-01-518-0146>

**Mounting Type:**

Frame

**Intake Connection Type:**

Round flange

**Media For Which Designed:**

Hydraulic fluid

**Pumping Element Type:**

Piston

**End Application:**

Uss frank cable

**Operating Speed At Rated Capacity:**

3100.00 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Clockwise and counterclockwise

**Reciprocating Stroke Type:**

Variable

**Product Name:**

Axial piston variable displacement series 90 pump

**Special Features:**

Crane cgo x sail cap 10000 lbs. Product series: 90 closed circuit. Type and rotation: left hand pump. Displacement: 130 cc/rev (7.930 cubic inches per rev). Control: electrical displacement with ms connector. Pressure regulation: pressure limiter (pl) in port a and b below 450 bar (ref pib 2000-14). Auxiliary mounting pad: none (standard). Twin end cap ports. Filtration: suction (standard). Displacement limitation: limitation both sides (factory set at displacement). Shaft configuration: 13t 8/16 pitch. Charging system: 34 cc/rev (2.07 cubic inch/rev). Control orifice: .040 inch diameter. Special hardware features: standard valve plate 180 cc. High pressure setting for port a: 200 bar (2901 psi). High pressure setting for port b: 20 bar (2901 psi). Charge pressure setting: 24.133 bar (350 psi) (standard).

**Type/model Designation:**

90l130ka5nn80s4f1h04gba202024

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400