

View Online at <https://aerobasegroup.com/nsn/4320-01-526-5278>

**Prime Mover Cooling Medium:**

Liquid

**Current Type:**

Dc

**Media For Which Designed:**

Water, fresh

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

350.0 gallons per minute

**Pumping Element Operating Position:**

Vertical

**Prime Mover Type:**

Diesel engine

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

5.5 horsepower

**Voltage In Volts:**

24.0

**Special Features:**

This pumping unit can be transported for short distances by means of a towing vehicle or, loaded on a flatbed trailer for long distances. It consists of john deere pe4024tf270 diesel engine and a self priming centrifugal pump loaded on a two wheel frame assembly. An internal fuel supply supplies fuel to the diesel engine.

**Special Test Features:**

Engine is capable of being operated on jp-8, jp-5, df-1, df-2 and df-a fuels.

**Specification Data:**

81349-mil-prf-53051b, type i, size 1. Government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400

**Mil-std (military Standard):**

Mil-prf-53051b spec.