

View Online at <https://aerobasegroup.com/nsn/4320-01-529-0758>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Current Type:**

Ac

**Media For Which Designed:**

Water, distilled

**Pump Quantity:**

1

**End Application:**

S-500 fl-2, shipalt cg class

**Maximum Discharge Flow Rate:**

15.0 gallons per minute

**Operating Speed At Rated Capacity:**

3500.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Impeller Quantity:**

1

**Pump Basic Material:**

Steel

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

4.4

**Prime Mover Power Rating:**

3.0 horsepower

**Product Name:**

Pump and motor assembly with mounting plate (distiller distillate cg class)

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Size: 1 x 1.25 x 675. Basic spec: mil-p-18472 and mil-m-17060e amend. 1. Rated capacity: 15 gpm. Tdh rating 138 feet. Shut off head: 155 feet. Fluid: fresh water. Specific gravity: 1.0. Suction pressure: 1.6 psia. Suction temperature: 95 f. Motor; duty: continuous, speed class: constant. Cooling method: fan.

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400