

View Online at <https://aerobasegroup.com/nsn/4320-01-529-0758>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Current Type:

Ac

Media For Which Designed:

Water, distilled

Pump Quantity:

1

End Application:

S-500 fl-2, shipalt cg class

Maximum Discharge Flow Rate:

15.0 gallons per minute

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Impeller Quantity:

1

Pump Basic Material:

Steel

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

4.4

Prime Mover Power Rating:

3.0 horsepower

Product Name:

Pump and motor assembly with mounting plate (distiller distillate cg class)

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Size: 1 x 1.25 x 675. Basic spec: mil-p-18472 and mil-m-17060e amend. 1. Rated capacity: 15 gpm. Tdh rating 138 feet. Shut off head: 155 feet. Fluid: fresh water. Specific gravity: 1.0. Suction pressure: 1.6 psia. Suction temperature: 95 f. Motor; duty: continuous, speed class: constant. Cooling method: fan.

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400