

View Online at <https://aerobasegroup.com/nsn/4320-01-533-4474>

Prime Mover Quantity:

1

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Maximum Discharge Flow Rate:

20.0 gallons per minute

Total Head:

46.200 feet

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Impeller Quantity:

1

Prime Mover Type:

Electric motor

Prime Mover Power Rating:

1.5 horsepower

Product Name:

Pump, recirculating

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Pump size 1.25 x 1 x 7 close-coupled with 1.25in. Suction class 150 flange ansi b16.5, 1in. Discharge class 150 flange ansi b16.5; pump impeller finish diameter 4in.; orifice diameter .687in.; submergence flooded; suction temperature 110 degrees f; rated input .7 (est); max. Rated input at any condition 1.0 (est); hydrostatic test pressure 50 psi/30 min.; motor constant speed, continuous duty per mil-m-1760e; output 1/5 bhp; speed (sych) 3600 rpm; windings squirrel cage; permissible ambient temperature 50 degrees c; enclosure tefc; bearings ball; frame 184tncz; motor mounting horizontal

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400