

View Online at <https://aerobasegroup.com/nsn/4320-01-533-4801>

Prime Mover Quantity:

1

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Maximum Discharge Flow Rate:

25.0 gallons per minute

Total Head:

139.000 feet

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Impeller Quantity:

1

Prime Mover Type:

Electric motor

Prime Mover Power Rating:

5.0 horsepower

Product Name:

Pump, edg recirculating

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Pump size 1.25 x 1-7 close-coupled with 1.25in. Suction class 150 flange ansi b16.5, 1in. Discharge class 150 flange ansi b16.5; submergence flooded; suction temperature 40-100 degrees f; hydrostatic test pressure 100 psi/30 min.; impeller finish diameter 6.25in; orifice diameter .687in; motor horizontal continuous duty, constant speed built per mil-m-1760e; speed (sych) 3600 rpm; windings squirrel cage; permissible ambient temperature 50 degrees c; enclosure tefc; bearings ball; frame 213tncz

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400