NSN 4320-01-534-5791

Centrifugal Pump Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-534-5791

End	Δ	nı	nli	ca	tic	'n.
LIIU	\boldsymbol{n}	v	UII	ca	uч	,,,,

Nha: water mist fire fighting transfer pump, 2.5 x 2 x 7

Product Name:

Pump, transfer

Special Features:

Pump characteristics: 2.5 x 2 - 7 close coupled horizontal pump; capaci type 150 gpm; total rated head 116 ft.; suction lift flooded; specific gravi type 1.0; liquid pumped fresh water; suction temperature -2 degrees c to 38 degrees c; 2in. Discharge ansi b16.5 class 150 flange, 2.5in. Suction ansi b16.5 class 150 flange; hydrostatic test pressure 90 psig; motor characteristics: 7.5 hp horizontal continuous du type 3 phase 60 hertz 440 volt ac constant speed motor; speed (sych) 3600 rpm; squirrel cage windings; permissible ambient temperature 50 degrees c; enclosure tefc; design class b, b dim. Is longer than max. Allowable due to use of l215 frame

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400