

View Online at <https://aerobasegroup.com/nsn/4320-01-535-0559>

Mounting Type:

Unthreaded hole

Intake Connection Quantity:

1

Discharge Connection Quantity:

1

Current Type:

Ac

Media For Which Designed:

Alcohol and water, fresh

Environmental Protection:

Explosion proof

End Application:

P3c orion fuselage

Maximum Discharge Flow Rate:

0.0833 gallons per minute

Discharge Pressure:

30.0 pounds per square inch gage

Prime Mover Type:

Electric motor

Current Rating In Amps:

4.5

Intake Connection Thread Size And Series/type Designator:

0.750-16 unf

Product Name:

Pump-electric motor driven alcohol and water

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Operating pressure 28 psi min; proof pressure 45 psi; rated flow 5 gph at 30 porm 2 psi at 70 degrees f to 90 degrees f, 16.9 inch hg, absolute ambient pressure; relief valve removed; electrical duty intermittent; voltage 380/420 cps; operating current 1.4 amps max, locked rotor current 4.5 amps max; explosion proof as required by 421672; thermal protection as required by 421672; power factor removed; outlet fluid port 9/16-18 nf-3 thread per and10050 or ms33649; seal drain 7/16-20 nf-3 thread per and10050 or ms33649; electrical connector bendix scintilla pto2e-8-2p in accordance with mil-c-2648 (asg) ; fluid mixture 80 pct isopropyl alcohol and 20 pct tap water; temperature m65.0 to 165.0 degrees f

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400