

View Online at <https://aerobasegroup.com/nsn/4320-01-537-0025>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Unthreaded hole

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

End Application:

Pump, centrifugal p/n 998-1107-f-05

Maximum Discharge Flow Rate:

460.0 gallons per minute

Operating Speed At Rated Capacity:

3600.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Unpackaged Unit Length:

33.000 inches

Unpackaged Unit Height:

17.400 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

20.0

Prime Mover Power Rating:

30.0 horsepower

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Manufacturer drawing nomenclature 4 x 3 - 7 defines suction size of 4 inches, discharge size of 3 inches, and impeller diameter of 7 inches

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400