

View Online at <https://aerobasegroup.com/nsn/4320-01-544-6958>

Mounting Type:

Bracket

Cylinder Quantity:

5

Exhaust Pressure:

41.0 pounds per square inch gage

Intake Connection Quantity:

1

Discharge Connection Quantity:

1

Current Type:

Dc

Media For Which Designed:

Water, fresh and water, salt

Power Drive Operating Pressure:

25.0 pounds per square inch gage

Environmental Protection:

Watertight

Pumping Element Type:

Diaphragm

Cooling Method:

Water cooled

Maximum Discharge Flow Rate:

13.0 liters per minute

Discharge Pressure:

40.6 pounds per square inch gage

Total Head:

2.0 meters

Pumping Element Operating Position:

Vertical

Volume Control Type:

Pressure compensation

Inclosure Type:

Fully enclosed

Features Provided:

Self-priming and integral relief valve

Voltage In Volts:

12.0 and 24.0

Special Features:

Dry running w/o damage; quick disconnect fittings; nylon body; polypropopylene valve housing; santoprene valves; maximum liquid temp 50 degrees c; stainless steel fasteners; intermittent duty cycle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400