

View Online at <https://aerobasegroup.com/nsn/4320-01-545-7027>

**End Application:**

Light amphibious resupply craft (larc v) slep

**Product Name:**

Pump, hydraulic

**Extra Long Reference Number:**

Pgp511b0160aa1h2nd7d5c-511a0070xb1d5b1b1

**Special Features:**

Tandem type double gear pump; front pump: 16.0 displacement, 69 bar max. Cont. Pressure, 500-2400 rpm speed rate, operating temp range: 0 degrees c-80 degrees c continuous, -20 degrees c cold start, 100 degrees c max. Intermittent; single nitrile shaft seal, ccw rotation; rear pump: 7.0 displacement, 172 bar max. Cont. Pressure, operating temp range: 0 degrees c-80 degrees c continuous, -20 degrees c cold start, 100 degrees c max. Intermittent; single nitrile shaft seal, ccw rotation; sae involute spline, 9 teeth-16/32 pitch, flat root side fit; ports: sae nbr 20 str. Thr. Port, 1-5/8in.-12un-2b thd for 1-1/4in. O.D. Tube (inlet); sae nbr 12 str.Thr. Port 1-1/16in.-12un-2b thread for 3/4in. O.D. Tube (2 outlets)

**Reference Number Differentiating Characteristics:**

As differentiated by extra long reference number

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400