

View Online at <https://aerobasegroup.com/nsn/4320-01-565-2596>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Water, fresh and water, salt and water, waste

Mounting Type:

Base

Discharge Connection Quantity:

1

Discharge Connection Type:

Flared tube

Current Type:

Dc

Media For Which Designed:

Water, fresh and water, salt and water, waste

Environmental Protection:

Explosion proof

Pump Quantity:

1

Cooling Method:

Water-air cooled

Accessory Components:

Electric power cable

End Application:

Offshore raiding craft

Maximum Discharge Flow Rate:

25.0 gallons per minute

Total Head:

2.0 meters

Suction Lift:

0.1 meters

Pumping Element Operating Position:

Vertical

Volume Control Type:

Rotary

Rotary Pump Design:

Vane

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

108.0 millimeters

Unpackaged Unit Width:

108.0 millimeters

Unpackaged Unit Height:

152.4 millimeters

Pump Basic Material:

Plastic

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

4.8 and 7.0

Features Provided:

Submersible

Prime Mover Power Rating:

95.2 watts

Voltage In Volts:

12.0 and 13.6

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400