

View Online at <https://aerobasegroup.com/nsn/4320-01-582-0006>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded external

Current Type:

Ac

Media For Which Designed:

Liquid

Pump Quantity:

1

End Application:

Spacelift range system (slrs) weather radar

Maximum Discharge Flow Rate:

30.0 gallons per minute

Total Head:

41.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

0.750 npt

Intake Connection Thread Size And Series/type Designator:

1.000 npt

Prime Mover Power Rating:

0.3 horsepower

Product Name:

Series 5.5 pump

Voltage In Volts:

115.0 and 230.0 and 460.0

Phase:

Single/three

Special Features:

Max int presure 50 psi; maximum liquid temp 190 degrees f; pump employs an involute design with a closed impeller magnet assembly

Frequency In Hertz:

50.0 and 60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400