

View Online at <https://aerobasegroup.com/nsn/4320-01-582-0006>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded external

**Current Type:**

Ac

**Media For Which Designed:**

Liquid

**Pump Quantity:**

1

**End Application:**

Spacelift range system (slrs) weather radar

**Maximum Discharge Flow Rate:**

30.0 gallons per minute

**Total Head:**

41.000 feet

**Operating Speed At Rated Capacity:**

3450.0 revolutions per minute

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

0.750 npt

**Intake Connection Thread Size And Series/type Designator:**

1.000 npt

**Prime Mover Power Rating:**

0.3 horsepower

**Product Name:**

Series 5.5 pump

**Voltage In Volts:**

115.0 and 230.0 and 460.0

**Phase:**

Single/three

**Special Features:**

Max int presure 50 psi; maximum liquid temp 190 degrees f; pump employs an involute design with a closed impeller magnet assembly

**Frequency In Hertz:**

50.0 and 60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400