# NSN 4320-01-600-8899

Reciprocating Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-600-8899

## Mounting Type:

Base

Cylinder Quantity:

2

Intake Connection Type:

Threaded internal

- **Discharge Connection Quantity:**
- 1

#### **Discharge Connection Type:**

Threaded internal

#### **Pumping Element Type:**

Diaphragm

Maximum Discharge Flow Rate:

70.0 gallons per minute

#### **Discharge Pressure:**

125.0 pounds per square inch gage

#### Pump Reciprocating Design:

Double acting

#### **Operation Method:**

Powered

### Discharge Connection Thread Size And Series/type Designator:

1.0 inch nptf

### Intake Connection Thread Size And Series/type Designator:

1.0 inch nptf

### **Product Name:**

Heavy duty flap valve, type 1, air-operated double-diaphragm pump

### **Special Features:**

Materials: manifold, elbow, and outer chamber: 356-t6a (aluminum), inner chamber, outer diaphragm plate, intermediate housing, and air valve cap: al380dc (aluminumdie cast), inner diaphragm and hardware: plated steel, diaphragm rod: 416ss (stainless steel), valve seat: stainless steel, diaphragm, flap valve, seal/manifold seal: nitrite, air valve: conductive hdpe.Shipping weight: 48.0 pounds.

## Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A19400