

View Online at <https://aerobasegroup.com/nsn/4320-01-617-7587>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Liquid

Mounting Type:

Trailer

Intake Connection Quantity:

3

Discharge Connection Quantity:

3

Current Type:

Dc

Media For Which Designed:

Fuel

Environmental Protection:

Waterproof

Pump Quantity:

1

Cooling Method:

Water-air cooled

Accessory Components:

Lifting and tie-down provisions and prime mover controller

Special Handling Feature:

Flammable

Maximum Discharge Flow Rate:

600.0 gallons per minute

Discharge Pressure:

250.0 pounds per square inch gage

Total Head:

350.0 feet

Operating Speed At Rated Capacity:

2000.0 revolutions per minute

Unpackaged Unit Length:

144.52 inches

Unpackaged Unit Width:

85.58 inches

Unpackaged Unit Height:

97.64 inches

Pump Basic Material:

Aluminum

Prime Mover Type:

Diesel engine

Inclosure Type:

Open

Features Provided:

Self-priming

Prime Mover Power Rating:

149.0 horsepower

Product Name:

Fuel pump, centrifugal

Voltage In Volts:

24.0

Surface Treatment:

Anodize

Surface Treatment:

Anodized

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A19400