

View Online at <https://aerobasegroup.com/nsn/4320-01-617-7587>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Liquid

**Mounting Type:**

Trailer

**Intake Connection Quantity:**

3

**Discharge Connection Quantity:**

3

**Current Type:**

Dc

**Media For Which Designed:**

Fuel

**Environmental Protection:**

Waterproof

**Pump Quantity:**

1

**Cooling Method:**

Water-air cooled

**Accessory Components:**

Lifting and tie-down provisions and prime mover controller

**Special Handling Feature:**

Flammable

**Maximum Discharge Flow Rate:**

600.0 gallons per minute

**Discharge Pressure:**

250.0 pounds per square inch gage

**Total Head:**

350.0 feet

**Operating Speed At Rated Capacity:**

2000.0 revolutions per minute

**Unpackaged Unit Length:**

144.52 inches

**Unpackaged Unit Width:**

85.58 inches

**Unpackaged Unit Height:**

97.64 inches

**Pump Basic Material:**

Aluminum

**Prime Mover Type:**

Diesel engine

**Inclosure Type:**

Open

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

149.0 horsepower

**Product Name:**

Fuel pump, centrifugal

**Voltage In Volts:**

24.0

**Surface Treatment:**

Anodize

**Surface Treatment:**

Anodized

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A19400