

View Online at <https://aerobasegroup.com/nsn/4320-01-629-5762>

Prime Mover Quantity:

2

Mounting Type:

Foot

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

2

Discharge Connection Type:

Threaded internal

Power Drive Operating Pressure:

120.0 pounds per square inch gage

Pump Quantity:

1

End Application:

Endeavor, grey water system

Maximum Discharge Flow Rate:

150.0 gallons per minute

Discharge Pressure:

120.0 pounds per square inch gage

Suction Lift:

18.0 feet

Pumping Element Operating Position:

Horizontal

Pump Basic Material:

Aluminum

Prime Mover Type:

Pneumatic motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

2.0-11 bsp.Tr int

Intake Connection Thread Size And Series/type Designator:

2.0-11 bsp.Tr int

Product Name:

Air operated diaphragm pump

Special Features:

Repair kit required is p/n dof525 and consists of 2 tpe diaphragms, 4 tpe seats, 4 acetal balls

Type/model Designation:

Husky 2150

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400