

View Online at <https://aerobasegroup.com/nsn/4320-01-630-3625>

Prime Mover Quantity:

1

Mounting Type:

Foot

Intake Connection Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Liquid

Pump Quantity:

1

Maximum Discharge Flow Rate:

20.0 gallons per minute

Discharge Pressure:

11.5 pounds per square inch gage

Total Head:

1200.0 feet

Suction Lift:

25.0 feet

Pumping Element Operating Position:

Vertical

Centrifugal Pump Impeller Quantity:

1

Volume Control Type:

Servo motor

Control Location:

Center

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

1.0 npt

Prime Mover Power Rating:

16.7 horsepower

Product Name:

Supplied with 25-foot cord; 1/6 hp oil-filled motor, 1-inch fnpt discharge connection with garden hose adapter

Voltage In Volts:

230.0

Special Features:

Submersible pump, series 5-mspr, 1/6 hp, 230 vac, 1-inch fnpt discharge, 25-foot cord

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400