# NSN 4330-00-019-4578

Fluid Filter - Page 1 of 2



## Mounting Type:

Threaded hole top

## Mounting Hole Quantity:

2

## Body Outside Diameter:

3.450 inches

## **Body Height:**

8.050 inches

## **Filtration Rating In Microns:**

10.0

## Drop Pressure:

20.0 pounds per square inch

## **Distance Between Mounting Hole Centers:**

3.188 inches

## **Design Type:**

Reusable

## Tempurature Rating:

Between -40.0 degrees fahrenheit and 375.0 degrees fahrenheit

## Features Provided:

By-pass valve and drain plug

## Filtering Element Quantity:

1

## Mounting Facility Thread Series Designator:

Unc

## Maximum Operating Pressure:

100.0 pounds per square inch

## Filtering Media Design:

Pleated single filtering media response

## First Intake Connection Type:

Threaded internal pipe head side

## Mounting Facility Thread Size:

0.375 inches

## First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

## First Intake Thread Series Designator:

Nptf

## First Intake Thread Size:

1.000 inches

## First Intake Thread Direction:

**Right-hand** 

## Filtering System For Which Designed:

Full flow or partial flow



# NSN 4330-00-019-4578

Fluid Filter - Page 2 of 2

**Special Features:** Spin-on type element Material: Steel body Media For Which Designed: Fuel/oil, hydrocarbon Style Designator: Unthreaded shell Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A24000

