## NSN 4330-00-138-2209

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-00-138-2209 **Mounting Type:** Threaded hole top **Mounting Hole Quantity:** 2 **Body Length:** 3.820 inches **Body Width:** 1.880 inches **Body Height:** 7.600 inches **Filtration Rating In Microns:** 10.0 **Drop Pressure:** 7.0 pounds per square inch **Distance Between Mounting Hole Centers:** 1.880 inches **Design Type:** Reusable **Tempurature Rating:** Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit **Features Provided:** By-pass valve and differential pressure indicator **Filtering Element Quantity: Mounting Facility Thread Series Designator:** Unc **Maximum Operating Pressure:** 100.0 pounds per square inch Filtering Media Design: Pleated single filtering media response **First Intake Connection Type:** Threaded internal pipe head side **Mounting Facility Thread Size:** 0.250 inches First Discharge Connection Relationship To Intake Connection: Identical to first intake connection **Distance From Bottom Of Body To Center Of Inlet:** 6.760 inches First Intake Thread Series Designator:

Npt

First Intake Thread Size:

0.750 inches

## NSN 4330-00-138-2209

Fluid Filter - Page 2 of 2



First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
Spin-on type element; 5 psi bypass; pressure gauge on indicator port no. 3
Material:
Rubber buna n seal
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Tee type (hydraulic)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24000