

View Online at <https://aerobasegroup.com/nsn/4330-00-454-8112>

**Mounting Type:**

Threaded hole top

**Mounting Hole Quantity:**

4

**Filtration Rating In Microns:**

10.0

**Drop Pressure:**

6.7 pounds per square inch

**Distance Between Mounting Hole Centers:**

2.380 inches and 6.750 inches

**Design Type:**

Reusable

**Tempurature Rating:**

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Unit Quantity:**

2

**Features Provided:**

By-pass valve and differential pressure indicator

**Filtering Element Quantity:**

2

**Mounting Facility Thread Series Designator:**

Unc

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Filtering Media Design:**

Pleated single filtering media response

**First Intake Connection Type:**

Threaded internal pipe head side

**Mounting Facility Thread Size:**

0.375 inches

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**First Intake Thread Series Designator:**

Nptf

**First Intake Thread Size:**

1.500 inches

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

15 psi bypass; suction pressure gauge on indicator pot no. 1

**Material:**

Steel sediment bowl

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Surface Treatment:**

Zinc sediment bowl

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000