NSN 4330-00-788-7441

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4330-00-788-7441

| Mounting Type: | | | | | |
|---|--|--|--|--|--|
| Unthreaded hole base | | | | | |
| Mounting Hole Diameter: | | | | | |
| 0.204 inches | | | | | |
| Mounting Hole Quantity: | | | | | |
| 2 | | | | | |
| Body Outside Diameter: | | | | | |
| 4.000 inches | | | | | |
| Body Height: | | | | | |
| 2.500 inches | | | | | |
| Differential Pressure: | | | | | |
| 75.0 pounds per square inch | | | | | |
| Distance Between Mounting Hole Centers: | | | | | |
| 4.480 inches | | | | | |
| Design Type: | | | | | |
| Limited | | | | | |
| Features Provided: | | | | | |
| By-pass valve | | | | | |
| Filtering Element Quantity: | | | | | |
| 1 | | | | | |
| Maximum Operating Pressure: | | | | | |
| 350.0 pounds per square inch | | | | | |
| Filtering Media Design: | | | | | |
| Pleated single filtering media response | | | | | |
| First Intake Connection Type: | | | | | |
| Threaded internal pipe bottom side | | | | | |
| First Discharge Connection Relationship To Intake Connection: | | | | | |
| Identical to first intake connection | | | | | |
| First Intake Thread Series Designator: | | | | | |
| Npt | | | | | |
| First Intake Thread Size: | | | | | |
| 0.250 inches | | | | | |
| First Intake Thread Direction: | | | | | |
| Right-hand | | | | | |
| Filtering System For Which Designed: | | | | | |
| Full flow | | | | | |
| Material: | | | | | |
| Stainless steel filtering medium | | | | | |
| Style Designator: | | | | | |
| Body and cover assembly (bolted flange) | | | | | |
| Shelf Life: | | | | | |
| N/a | | | | | |

NSN 4330-00-788-7441

Fluid Filter - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A24000